MURR ELEKTRONIK
stay connected

## RMMER 11/24 AC/DC OUTPUT RELAY


IN: 24 VAC/DC - OUT: 250 VAC/DC / 5 A


1 relay; 1 NC contact
5 A
24 V AC/DC
Screw terminals

Link til produkt

### Illustrasjon






Produktet kan avvike fra bildet

### Handelsinformasjon

| | |
|---|---|
| ECLASS-6.0 | 27371001 |
| ECLASS-6.1 | 27371601 |
| ECLASS-7.0 | 27371601 |
| ECLASS-8.0 | 27371601 |
| ECLASS-9.0 | 27371601 |
| ECLASS-10.1 | 27371601 |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.
All informasjon gis uten ansvar for eventuelle feil og mangler. 29.03.2024

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27371601 |
| ECLASS-12.0 | 27371601 |
| ETIM-5.0 | EC001437 |
| GTIN | 4048879027441 |
| Pakkestørrelse | 1 |
| Tolltariffnummer | 85364900 |
| **Electrical data \| Input** | |
| Input voltage AC | 24 V |
| Input voltage AC min. | 19,2 V |
| Input voltage AC max. | 30 V |
| Input voltage DC | 24 V |
| Input voltage DC min. | 19,2 V |
| Input voltage DC max. | 30 V |
| Input current | 15 mA |
| **Electrical data \| Output** | |
| Utilization category AC-15 (EN IEC 60947-5-1) | 3 A @ 24 V, 3 A @ 110 V, 3 A @ 230 V |
| Utilization category DC-13 (EN IEC 60947-5-1) | 1,5 A @ 24 V, 0,3 A @ 110 V, 0,15 A @ 230 V |
| Switching frequency max. | 15 Hz |
| Power rating AC max. | 1500 VA |
| Power rating DC max. | 120 W |
| Switching voltage AC max. | 250 V |
| Switching voltage DC max. | 250 V |
| Switching current DC | 1 mA |
| Switching current max. | 5 A |
| Switching capacity AC-12 (EN IEC 60947-5-1) | 5 A (24/110/230 V AC) |
| **Diagnostics** | |
| Status indication LED | yellow |
| **Device protection** | |
| Condition lifetime | load-dependent |
| **Device protection \| Electrical** | |
| Rated surge voltage | 1,5 kV |
| Electrical lifetime | 100000000 Cycles |
| **Device protection \| Mechanical** | |
| Mechanical endurance | 100000000 Cycles |
| **Mechanical data** | |
| Drop-out time max. | 10 ms |
| Response time max. | 10 ms |
| Bounce time max. | 1 ms |
| **Mechanical data \| Material data** | |
| Material contact | AG Ni hv |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | Mounting rail TH35, G32, (EN 60715) |
| Height | 56 mm |
| Width | 12 mm |
| Depth | 65 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.
All informasjon gis uten ansvar for eventuelle feil og mangler. 29.03.2024

| Connection type 2 | |
|---|---|
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| No. of poles | 2 |
| PIN 1 | 11 |
| PIN 2 | 12 |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| No. of poles | 2 |
| PIN 1 | A 1 |
| PIN 2 | A 2 |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.
All informasjon gis uten ansvar for eventuelle feil og mangler. 29.03.2024