

MPOT POTENTIOMETER MODULE

10K-Ohm/270 degree

270° potentiometer

10 kΩ


The 10-turn potentiometer has a decimal scale and locking lever

The potentiometer modules are fitted with standard values. They are available as 270° potentiometer and as 10-turn potentiometer with fine adjustment. They can be operated with 10 V DC or 24 V DC. A resistor reduces the voltage so that a 24 V DC voltage can be reduced to operate between approx. 0...11 V. The connection is via terminals.

Link to Product

Illustration





Product may differ from Image

| Commercial data | | |
|-----------------|----------|---|
| ECLASS-6.0 | 27371227 | |
| ECLASS-6.1 | 27371227 | |
| ECLASS-7.0 | 27371227 | |
| ECLASS-8.0 | 27371227 | |
| ECLASS-9.0 | 27371227 | |
| ECLASS-10.1 | 27371227 | |
| ECLASS-11.1 | 27371227 | |
| ECLASS-12.0 | 27371227 | |
| ETIM-5.0 | EC001027 | - |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-20

Murrelektronik A.S. | Christian August Thorings vei 7 | 4033 Stavanger | Fon +47 32 1790-80 | Fax +47 32 1790-90 | shop@murrelektronik.no | shop.murrelektronik.no



| customs tariff number | 85334010 |
|--|---------------------------|
| GTIN | 4048879041683 |
| Packaging unit | 1 |
| Electrical data | |
| Power max. | 1 W |
| Linearity | ±3 % |
| Resistance | 10 kΩ |
| Resistance tolerance | 20 % |
| Electrical data Input | |
| Power loss max. | 0,25 W |
| Mechanical data Mounting data | |
| Mounting method | geschnappt |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height | 75 mm |
| Width | 45 mm |
| Depth | 65 mm |
| Environmental characteristics Climatic | |
| Operating temperature min. | O° O |
| Operating temperature max. | 0° 00 |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-20

Murrelektronik A.S. | Christian August Thorings vei 7 | 4033 Stavanger | Fon +47 32 1790-80 | Fax +47 32 1790-90 | shop@murrelektronik.no | shop.murrelektronik.no