

EUROCARD HOLDER

SKPD form D, 230V, 32-pole, 234x160mm

screw terminal 32-pole 230 V AC

To insert the card first press down the 2 yellow buttons. Then slide the Eurocard into the guide slots pushing until fully engaged. The card is now locked into position. It can be removed by pressing down on the 2 yellow buttons.

Link to Product

Illustration



Product may differ from Image



Commercial data	
ECLASS-6.0	27260710
ECLASS-6.1	27260704
ECLASS-7.0	27440402
ECLASS-8.0	27440402
ECLASS-9.0	27440402
ECLASS-10.1	27440402
ECLASS-11.1	27460201
ECLASS-12.0	27460201
ETIM-5.0	EC002780
customs tariff number	85366990
GTIN	4048879040051
Packaging unit	1
Electrical data Supply	
Operating voltage AC	230 V
Operating current max.	4 A
Installation	
Connection cross-section solid min.	0,25 mm²
Connection cross-section solid max.	4 mm²
Connection cross-section stranded/fine-stranded min.	0,5 mm²

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-10

Width

Depth



Connection cross-section stranded/fine-2,5 mm² stranded max. Installation | Connection Connection Screw terminals SK Installation | Pin assignment 32 No. of poles Device protection | Media Flame resistance flame retardant Mechanical data | Material data Material housing Plastic Mechanical data | Mounting data Mounting method screwed Suitable for mounting type mounting rail Height 63 mm

274 mm

167 mm