

MODLINK MSDD SINGLE COMBI INSERT USA NEMA 5-15

1xRJ45 female/female

1 × NEMA 5-15 (plug-solder connection)  
1 × RJ45, 8-pole metal, CAT5e (female/female)

Link to Product

Illustration



Product may differ from Image



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27182806      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC000020      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879037204 |
| Packaging unit                           | 1             |
| Mechanical data   Mounting data          |               |
| Height                                   | 88 mm         |
| Width                                    | 51 mm         |
| Depth                                    | 30 mm         |
| Environmental characteristics   Climatic |               |
| Storage temperature min.                 | 5 °C          |
| Storage temperature max.                 | 40 °C         |
| USA                                      |               |
| Connection geometry                      | 4.8 x 0.5 mm  |

|                                       |                        |
|---------------------------------------|------------------------|
| Operating voltage AC                  | 125 V                  |
| Operating current                     | 15 A                   |
| Connection                            | Plug-solder connection |
| No. of poles                          | 2 + PE                 |
| Protection contact present            | yes                    |
| <b>RJ45</b>                           |                        |
| Operating voltage AC max. (UL-listed) | 30 V                   |
| Operating voltage DC max. (UL-listed) | 42,4 V                 |
| Current operating max. (UL)           | 175 mA                 |
| Family construction form              | RJ45                   |
| Family type Back side                 | RJ45                   |
| Cable category min.                   | Cat5e                  |
| Looking techniques                    | Snap-in connector      |