

MOTOR SUPPRESSOR

RC, 3x575VAC/7,5kW

3× 575 V AC

RC

Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.

[Link til produkt](#)

Illustrasjon



Produktet kan avvike fra bildet



Handelsinformasjon	
ECLASS-6.0	27371013
ECLASS-6.1	27371013
ECLASS-7.0	27371013
ECLASS-8.0	27371013
ECLASS-9.0	27371013
ECLASS-10.1	27371013

ECLASS-11.1 27371013

ECLASS-12.0 27371013

ETIM-5.0 EC000197

GTIN 4048879019613

Pakkestørrelse 1

Tolltariffnummer 85363010

Electrical data | Supply

Power frequency 50 ... 60 Hz

Electrical data | Input

Input voltage AC 575 V

InstallationConnection cross-section stranded/fine-stranded min. 0,5 mm²**Installation | Connection**

Connection information Einzellitzen mit selbstsicherndem Gabelkabelschuh M4

Length single strands 250 mm

Device protection | Media

Flame resistance flame retardant

Mechanical data | Material data

Combustibility class housing (UL94) V-0

Material housing Plastic

Material potting compound 2-component epoxy

Mechanical data | Mounting data

Height 75 mm

Width 45 mm

Depth 42 mm

Environmental characteristics | Climatic

Operating temperature min. -20 °C

Operating temperature max. 60 °C