

MIIW ANALOG COUPLER COMPONENT

IN: 0(4)..20 mA - OUT: 0(4)..20 mA

INPUT: 0...20 mA
OUTPUT: 0...20 mA
Screw terminals
Input and output galvanically separated

[Link til produkt](#)

Illustrasjon



Produktet kan avvike fra bildet



Handelsinformasjon	
ECLASS-6.0	27210990
ECLASS-6.1	27210902
ECLASS-7.0	27210902
ECLASS-8.0	27210902
ECLASS-9.0	27210902
ECLASS-10.1	27210902

ECLASS-11.1 27210902

ECLASS-12.0 27210902

ETIM-5.0 EC002477

GTIN 4048879028431

Pakkestørrelse 1

Tolltariffnummer 85437090

Electrical data

Accuracy (of full scale) 0,5 %

Electrical data | Supply

Operating voltage DC 24 V

Operating voltage DC min. 19,2 V

Operating voltage DC max. 28,8 V

Operating current min. 50 mA

Operating current max. 70 mA

Electrical data | InputWorking resistance max. 250 Ω **Electrical data | Output**

Output current max. 0,025 A

Working resistance max. 500 Ω **Industrial communication**

Transmission frequency max. 500 Hz

Device protection | Electrical

Rated surge voltage 1,5 kV

Mechanical data | Mounting data

Mounting method geschnappt

Suitable for mounting type mounting rail, (EN 60715)

Height 91 mm

Width 6,2 mm

Depth 71 mm

Environmental characteristics | Climatic

Operating temperature min. -25 °C

Operating temperature max. 50 °C

Storage temperature min. -40 °C

Storage temperature max. 80 °C

Connection type 5

Connection Screw terminals SK

Family construction form terminal

Gender female

No. of poles 1

PIN 1 GD 1

Connection Screw terminals SK

Family construction form terminal

Gender female

No. of poles 1

PIN 1 In

Connection Screw terminals SK

Family construction form terminal

Gender female

No. of poles 1

PIN 1 + 24 V DC

Connection	Screw terminals SK
Family construction form	terminal
Gender	female
No. of poles	1
PIN 1	Out
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
No. of poles	1
PIN 1	GD