

LED-INDICATOR OPAC / YELLOW

LED-24V IP65

(yellow)  
24 V AC/DC  
The modules are suitable for wall thickness of 1.5...5.0 mm.

Link til produkt

Illustrasjon



Produktet kan avvike fra bildet



Handelsinformasjon

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27261590      |
| ECLASS-6.1       | 27261501      |
| ECLASS-7.0       | 27261501      |
| ECLASS-8.0       | 27261501      |
| ECLASS-9.0       | 27261501      |
| ECLASS-10.1      | 27261501      |
| ECLASS-11.1      | 27261501      |
| ECLASS-12.0      | 27261501      |
| ETIM-5.0         | EC000272      |
| GTIN             | 4048879041300 |
| Pakkestørrelse   | 10            |
| Tolltariffnummer | 85318070      |

Electrical data | Supply

|                           |        |
|---------------------------|--------|
| Operating voltage AC      | 24 V   |
| Operating voltage AC min. | 20,4 V |
| Operating voltage AC max. | 26,4 V |
| Operating voltage DC      | 24 V   |
| Operating voltage DC min. | 20,4 V |
| Operating voltage DC max. | 26,4 V |
| Current consumption min.  | 8 mA   |
| Current consumption max.  | 12 mA  |

Installation | Connection

Connection information Faston 2.8×0.8 mm

Device protection | Electrical

Degree of protection (EN IEC 60529) IP65

**Device protection | Media**

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

**Mechanical data**

|              |      |
|--------------|------|
| Diameter LED | 5 mm |
|--------------|------|

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Material housing | Plastic |
|------------------|---------|

**Mechanical data | Mounting data**

|                               |      |
|-------------------------------|------|
| Diameter front panel drilling | 9 mm |
|-------------------------------|------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
|----------------------------|--------|

|                            |       |
|----------------------------|-------|
| Operating temperature max. | 50 °C |
|----------------------------|-------|