

EMC SUPPRESSOR FOR MOTOR

RC 3 BU-575VVAC-7,5kW, AWG 22, VDR

3× 575 V AC

VDR

For DIN-rail mounting use Art.-No. 20900 adapter feet

Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.

[Link til produkt](#)

Illustrasjon



Produktet kan avvike fra bildet



| Handelsinformasjon |          |
|--------------------|----------|
| ECLASS-6.0         | 27371013 |
| ECLASS-6.1         | 27371013 |
| ECLASS-7.0         | 27371013 |
| ECLASS-8.0         | 27371013 |
| ECLASS-9.0         | 27371013 |

|                  |               |
|------------------|---------------|
| ECLASS-10.1      | 27371013      |
| ECLASS-11.1      | 27371013      |
| ECLASS-12.0      | 27371013      |
| ETIM-5.0         | EC000197      |
| GTIN             | 4048879015424 |
| Pakkestørrelse   | 10            |
| Tolltariffnummer | 85363010      |

**Electrical data | Supply**

|                 |               |
|-----------------|---------------|
| Power frequency | 10 ... 400 Hz |
|-----------------|---------------|

**Electrical data | Input**

|                  |       |
|------------------|-------|
| Input voltage AC | 575 V |
|------------------|-------|

**Installation**

|                                                      |          |
|------------------------------------------------------|----------|
| Connection cross-section stranded/fine-stranded min. | 0,35 mm² |
|------------------------------------------------------|----------|

**Installation | Connection**

|                        |                                                      |
|------------------------|------------------------------------------------------|
| Connection information | Einzellitzen mit selbstsicherndem Gabelkabelschuh M4 |
| Length single strands  | 230 mm                                               |

**Device protection | Media**

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

**Mechanical data | Material data**

|                                     |                   |
|-------------------------------------|-------------------|
| Combustibility class housing (UL94) | V-0               |
| Material housing                    | Plastic           |
| Material potting compound           | 2-component epoxy |

**Mechanical data | Mounting data**

|                            |                                |
|----------------------------|--------------------------------|
| Mounting method            | geschnappt                     |
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| Height                     | 43 mm                          |
| Width                      | 40 mm                          |
| Depth                      | 15 mm                          |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C  |