


MET SINGLE-PHASE CONTROL AND ISOLATION TRANSFORMER

P:1000VA IN:200/440VAC OUT:110/230VAC

Single-phase - Control and Isolation Transformers
1000 VA
Isolation class T 60/B
Condensation not permitted

[Link til produkt](#)

Illustrasjon



Produktet kan avvike fra bildet



Handelsinformasjon	
ECLASS-6.0	27031202
ECLASS-6.1	27031302
ECLASS-7.0	27031302
ECLASS-8.0	27031302
ECLASS-9.0	27031302
ECLASS-10.1	27031302

ECLASS-11.1	27031302
ECLASS-12.0	27031302
ETIM-5.0	EC002485
GTIN	4048879073929
Pakkestørrelse	1
Tolltariffnummer	85043180

Electrical data | Supply

Power frequency	50 ... 60 Hz
-----------------	--------------

Electrical data | Input

Input voltage 1 AC	200 V
Input voltage 2 AC	440 V
Input current at input voltage 1 AC	5,6 A
Input current at input voltage 2 AC	2,55 A
Inrush current at input voltage 1	124 A
Inrush current at input voltage 2	54 A
Short-circuit current at input voltage 1	158 A
Short-circuit current at input voltage 2	63 A

Electrical data | Output

Output voltage AC 1	110 V
Output voltage AC 2	230 V
Output voltage adjustable	yes
Power rating AC max.	1000 VA

Device protection | Electrical

Insulation test voltage input - output	4 kV
--	------

Mechanical data | Mounting data

Suitable for mounting type	Schlüssellochauhängung
Mounting dimension a	112 mm
Mounting dimension b	135 mm
Mounting dimension c	7 mm
Height	138 mm
Width	174 mm
Depth	160 mm
Diameter bore	7 mm
Length bore	15 mm

Environmental characteristics | Climatic

Operating temperature min.	-20 °C
Operating temperature max.	60 °C

Conformity

Product standard	EN 61558-1, EN 61558-2-4, EN 62041 category 0
------------------	---