

VALVE PLUG SUPPRESSOR FORM BI - 11MM 90°



RC and LED, 110VAC/DC/10VA/W

110 V AC/DC

RC + LED

Remove plug gasket when fitting adapter. Other LED colors on request.

Note PIN arrangement (PE at cable outlet of connector). 180° turned version on request.

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

ECLASS-6.0	27371013
ECLASS-6.1	27371013
ECLASS-7.0	27371013
ECLASS-8.0	27371013
ECLASS-9.0	27371013
ECLASS-10.1	27371013

ECLASS-11.1	27371013
ECLASS-12.0	27371013
ETIM-5.0	EC000197
GTIN	4048879012003
Pakkestørrelse	1
Tolltariffnummer	85363010

Electrical data

Capacity CX	20 ms
Holding power max.	10 W

Electrical data | Supply

Cut-off peak voltage max.	250 V
---------------------------	-------

Electrical data | Input

Input voltage AC min.	95 V
Input voltage AC max.	132 V
Input voltage DC min.	95 V
Input voltage DC max.	132 V

Diagnostics

Status indication LED	yellow
-----------------------	--------

Device protection | Media

Flame resistance	flame retardant
------------------	-----------------

Mechanical data | Material data

Coating contact	silver-plated
Color housing	black
Material housing	PA
Material contact	Bronze

Mechanical data | Mounting data

Height	15 mm
Width	63 mm
Depth	21,5 mm

Environmental characteristics | Climatic

Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Housing temperature max. (EN 61347-2-13)	130 °C