

**CAP FOR D-BOX M12 6-WAY 5-POLE**

No pot.-sep. 3m PUR/PVC-JB, 12x0,34+3x0,75

for 6-way distribution boxes, 5-pole

PUR/PVC


3.0 m

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27143423      |
| ECLASS-6.1       | 27279219      |
| ECLASS-7.0       | 27279219      |
| ECLASS-8.0       | 27279219      |
| ECLASS-9.0       | 27440108      |
| ECLASS-10.1      | 27440108      |
| ECLASS-11.1      | 27440108      |
| ECLASS-12.0      | 27440108      |
| ETIM-5.0         | EC002585      |
| GTIN             | 4048879058377 |
| Pakkestørrelse   | 1             |
| Tolltariffnummer | 85444290      |

**Electrical data | Supply**

|                    |     |
|--------------------|-----|
| Total current max. | 8 A |
|--------------------|-----|

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 33 mm |
| Width  | 48 mm |
| Depth  | 68 mm |

**Installation | Cable**

|                      |                       |
|----------------------|-----------------------|
| STOOW style jacket   | Hybrid, Signal, Power |
| Cable identification | 388                   |
| Cable Type           | 2                     |
| Jacket Color         | gray                  |

|                                                   |                                                                                                                                               |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Type of Certificate                               | cURus                                                                                                                                         |
| Amount stranding                                  | 1                                                                                                                                             |
| Stranding                                         | 3 wires twisted                                                                                                                               |
| Amount stranding (type 2)                         | 1                                                                                                                                             |
| Stranding (type 2)                                | 12 wires around Stranding combination twisted                                                                                                 |
| wire arrangement                                  | blue, brown, green-yellow, (gray-pink, white, red-blue, green, green-white, yellow, brown-green, gray, yellow-white, pink, brown-yellow, red) |
| Cable weight                                      | 162,8 g/m                                                                                                                                     |
| Material jacket                                   | PUR                                                                                                                                           |
| Shore hardness jacket                             | 87 ± 5 Shore A                                                                                                                                |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, silicone-free                                                                                              |
| Outer-diameter (jacket)                           | 9,2 mm                                                                                                                                        |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                                                                                                         |
| Material inner jacket                             | PVC                                                                                                                                           |
| Color (inner jacket)                              | gray                                                                                                                                          |
| Material wire insulation                          | PVC                                                                                                                                           |
| Amount wires                                      | 12                                                                                                                                            |
| Outer diameter insulation                         | 1,3 mm                                                                                                                                        |
| Outer diameter tolerance core insulation          | ± 5 %                                                                                                                                         |
| Shore hardness wire insulation                    | 43 ± 5 Shore D                                                                                                                                |
| Material properties wire insulation               | good machinability                                                                                                                            |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, silicone-free                                                                                              |
| Amount strands (wire)                             | 19                                                                                                                                            |
| Diameter of single wires                          | 0,15 mm                                                                                                                                       |
| Conductor crosssection (wire)                     | 0,34 mm <sup>2</sup>                                                                                                                          |
| Traversing distance (C-track)                     | 5 m @ 25 °C                                                                                                                                   |
| Material conductor wire                           | Stranded copper wire, bare                                                                                                                    |
| Conductor type (wire)                             | Strand class 5                                                                                                                                |
| Travel speed (C-track)                            | 3                                                                                                                                             |
| Material wire insulation (Power)                  | PVC                                                                                                                                           |
| Outer diameter wire insulation (Power)            | 1,8 mm                                                                                                                                        |
| Tolerance outer diameter wire insulation (Power)  | ±5 %                                                                                                                                          |
| Shore hardness wire insulation (Power)            | 43±5 Shore D                                                                                                                                  |
| Material properties wire insulation (Power)       | good machinability                                                                                                                            |
| Ingredient freeness wire insulation (Power)       | lead-free, cadmium-free, CFC-free, silicone-free                                                                                              |
| Amount strands wire (Power)                       | 42                                                                                                                                            |
| Diameter of single wires (Power)                  | 0,15 mm                                                                                                                                       |
| Wire conductor cross section (Power)              | 0,75 mm <sup>2</sup>                                                                                                                          |
| Material conductor wire (Power)                   | Stranded copper wire, bare                                                                                                                    |
| Conductor type wire (Power)                       | strand class 6                                                                                                                                |
| Max. rated voltage (conductor - conductor)        | 300 V                                                                                                                                         |
| Max. rated voltage (conductor - ground)           | 300 V                                                                                                                                         |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                                                                                                             |
| Current load capacity min. wire                   | 4 A                                                                                                                                           |
| Loop resistance                                   | 7,8 A                                                                                                                                         |
| Electrical resistance line constant wire          | 57 Ω/km                                                                                                                                       |
| Electrical resistance coating wire (Power)        | 26 Ω/km @20 °C                                                                                                                                |
| AC withstand voltage (wire - wire)                | 2 kV @ 60 s                                                                                                                                   |
| Power frequency withstand voltage (wire - jacket) | 2 kV @ 60 s                                                                                                                                   |
| Min. operating temperature (static)               | -30 °C                                                                                                                                        |
| Max. operating temperature (fixed)                | 80 °C                                                                                                                                         |
| Operating temperature min. (dynamic)              | -5 °C                                                                                                                                         |
| Operating temperature max. (dynamic)              | 70 °C                                                                                                                                         |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.  
All informasjon gis uten ansvar for eventuelle feil og mangler. 07.05.2024

|                          |                                                      |
|--------------------------|------------------------------------------------------|
| Flame resistance         | UL 1581 § 1090   UL 1581 § 1100 FT2   IEC 60332-2-2  |
| chemical resistance      | Good, application-related testing                    |
| Gasoline resistance      | Good, application-related testing                    |
| Oil resistance           | DIN EN 60811-404   Good, application-related testing |
| Bending radius (fixed)   | 5 x Outer diameter                                   |
| Bending radius (dynamic) | 10 x Outer diameter                                  |
| Travel speed (C-track)   | 2 Mio. @ 25 °C                                       |

**Connection type 2**

|                          |                |
|--------------------------|----------------|
| Family construction form | M12            |
| Gender                   | female         |
| Color contact carrier    | black          |
| Coding                   | A              |
| No. of poles             | 5              |
| PIN 1                    | +              |
| PIN 2                    | NC S 2         |
| PIN 3                    | -              |
| PIN 4                    | NO S 1         |
| PIN 5                    | PE             |
| Connection type 1        | X1-X8          |
| Family construction form | free cable end |
| Color contact carrier    | gray           |
| No. of poles             | 15             |
| Family construction form | M12            |
| Gender                   | female         |
| Color contact carrier    | black          |
| Coding                   | A              |
| No. of poles             | 5              |
| PIN 1                    | +              |
| PIN 2                    | NC S 2         |
| PIN 3                    | -              |
| PIN 4                    | NO S 1         |
| PIN 5                    | PE             |
| Family construction form | free cable end |
| Color contact carrier    | gray           |
| No. of poles             | 15             |