

**MODLINK MSDD DATA INSERT**

2xUSB-A female/female + 2xRJ45

RJ45; RJ45; USB; USB (A)  
2× RJ45, 8-pole metal, CAT5e (female/female)  
2× USB (female/female) form A

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27189217      |
| ECLASS-6.1       | 27189217      |
| ECLASS-7.0       | 27189217      |
| ECLASS-8.0       | 27189217      |
| ECLASS-9.0       | 27189217      |
| ECLASS-10.1      | 27182806      |
| ECLASS-11.1      | 27182806      |
| ECLASS-12.0      | 27182806      |
| ETIM-5.0         | EC002625      |
| GTIN             | 4048879037778 |
| Pakkestørrelse   | 1             |
| Tolltariffnummer | 85366990      |

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 60 mm |

**Environmental characteristics | Climatic**

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -20 °C |
| Storage temperature max. | 60 °C  |

**Shielding plate**

|                        |                  |
|------------------------|------------------|
| Connection information | Threaded hole M4 |
|------------------------|------------------|

Tightening torque 0,9 Nm

**USB**

|                                  |                   |
|----------------------------------|-------------------|
| Operating voltage AC             | 48 V              |
| Operating voltage DC             | 48 V              |
| Operating voltage DC (UL-listed) | 42,4 V            |
| Operating current max.           | 500 mA            |
| USB specification                | 2.0               |
| Data transmission rate max.      | 480 MBit/s        |
| Looking techniques               | Snap-in connector |

**RJ45**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat5e             |
| Looking techniques                    | Snap-in connector |