

**MODLINK MSDD DATA INSERT**

2×SUB-D9 female/female + 1×RJ45 + 1×USB-A

RJ45; USB (A); SUB-D9; SUB-D9

1× RJ45, 8-pole metal, CAT5e (female/female)

1× USB 2.0 (female/female) form A

2× SUB-D9 (female/female)

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27189217      |
| ECLASS-6.1       | 27189217      |
| ECLASS-7.0       | 27189217      |
| ECLASS-8.0       | 27189217      |
| ECLASS-9.0       | 27189217      |
| ECLASS-10.1      | 27182806      |
| ECLASS-11.1      | 27182806      |
| ECLASS-12.0      | 27182806      |
| ETIM-5.0         | EC002625      |
| GTIN             | 4048879037648 |
| Pakkestørrelse   | 1             |
| Tolltariffnummer | 85366990      |

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 45 mm |

**Environmental characteristics | Climatic**

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -30 °C |
| Storage temperature max. | 60 °C  |

**Shielding plate**

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Connection information                | Threaded hole M4                               |
| Tightening torque                     | 0,9 Nm                                         |
| <b>USB</b>                            |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage DC (UL-listed)      | 42,4 V                                         |
| Operating current max.                | 500 mA                                         |
| USB specification                     | 2.0                                            |
| Data transmission rate max.           | 480 MBit/s                                     |
| Looking techniques                    | Snap-in connector                              |
| <b>SUB-D9</b>                         |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | female                                         |
| Gender Rear                           | female                                         |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |
| <b>RJ45</b>                           |                                                |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | RJ45                                           |
| Family type Back side                 | RJ45                                           |
| Cable category min.                   | Cat5e                                          |
| Looking techniques                    | Snap-in connector                              |