

**MODLINK MSDD DATA INSERT**

1×SUB-D9fem./fem.+1×SUB-D9male/male+1×RJ45+1×USB-A

RJ45; USB (A); SUB-D9; SUB-D9

1× RJ45, 8-pole metal, CAT5e (female/female)

1× USB 2.0 (female/female) form A

1× SUB-D9 (female/female)

1× SUB-D9 (male/male)

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27189217      |
| ECLASS-6.1       | 27189217      |
| ECLASS-7.0       | 27189217      |
| ECLASS-8.0       | 27189217      |
| ECLASS-9.0       | 27189217      |
| ECLASS-10.1      | 27182806      |
| ECLASS-11.1      | 27182806      |
| ECLASS-12.0      | 27182806      |
| ETIM-5.0         | EC002625      |
| GTIN             | 4048879037631 |
| Pakkestørrelse   | 1             |
| Tolltariffnummer | 85366990      |

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 45 mm |

**Environmental characteristics | Climatic**

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -30 °C |
| Storage temperature max. | 60 °C  |

**Shielding plate**

|                        |                  |
|------------------------|------------------|
| Connection information | Threaded hole M4 |
| Tightening torque      | 0,9 Nm           |

**USB**

|                                  |                   |
|----------------------------------|-------------------|
| Operating voltage AC             | 48 V              |
| Operating voltage DC             | 48 V              |
| Operating voltage DC (UL-listed) | 42,4 V            |
| Operating current max.           | 500 mA            |
| USB specification                | 2.0               |
| Data transmission rate max.      | 480 MBit/s        |
| Looking techniques               | Snap-in connector |

**SUB-D9**

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | male                                           |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |

**RJ45**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat5e             |
| Looking techniques                    | Snap-in connector |