

**Modlink MSDD-set: Frame 4000-68112-0000000,**  
insert 4000-68000-1440000

[Link til produkt](#)

Illustrasjon



Produktet kan avvike fra bildet



| Handelsinformasjon |          |
|--------------------|----------|
| ECLASS-6.0         | 27189217 |
| ECLASS-6.1         | 27189217 |
| ECLASS-7.0         | 27189217 |
| ECLASS-8.0         | 27189217 |
| ECLASS-9.0         | 27189217 |
| ECLASS-10.1        | 27182806 |
| ECLASS-11.1        | 27182806 |
| ECLASS-12.0        | 27182806 |
| ETIM-5.0           | EC002625 |

GTIN 4048879036443

Pakkestørrelse 1  
Tolltariffnummer 85366990

**Frame**

Degree of protection (EN IEC 60529) IP65  
Operating temperature min. -10 °C  
Operating temperature max. 60 °C  
Storage temperature min. -25 °C  
Storage temperature max. 60 °C  
Suitable for installation wall thickness min. 1 mm  
Suitable for installation wall thickness max. 5 mm  
Coating housing KTL  
Material housing Fine zinc die casting

**Shielding plate**

Connection information Threaded hole M4  
Tightening torque 0,9 Nm

**USB**

Operating voltage AC 48 V  
Operating voltage DC 48 V  
Operating voltage AC max. (UL-listed) 30 V  
Operating voltage DC max. (UL-listed) 42,4 V  
Operating current 1,5 A  
USB specification 3.0  
Data transmission rate max. 5000 MBit/s  
Looking techniques Snap-in connector

**SUB-D9**

Operating voltage AC 48 V  
Operating voltage DC 48 V  
Operating voltage AC max. (UL-listed) 30 V  
Operating voltage DC max. (UL-listed) 42,4 V  
Operating current 3 A  
Current operating max. (UL) 175 mA  
Family construction form SUB-D9  
Family type Back side SUB-D9  
Gender female  
Gender Rear female  
Looking techniques Standard UNC 4-40 screw thread bolt (EN 60807)  
No. of poles 9

**RJ45**

Operating voltage AC max. (UL-listed) 30 V  
Operating voltage DC max. (UL-listed) 42,4 V  
Current operating max. (UL) 175 mA  
Family construction form RJ45  
Family type Back side RJ45  
Cable category min. Cat5e  
Looking techniques Snap-in connector