


**Modlink MSDD-set: Frame 4000-68123-0000000,**  
insert 4000-68000-0010000 + 4000-68000-0010000

Link til produkt

Illustrasjon



Produktet kan avvike fra bildet



| Handelsinformasjon |          |
|--------------------|----------|
| ECLASS-6.0         | 27189217 |
| ECLASS-6.1         | 27189217 |
| ECLASS-7.0         | 27189217 |
| ECLASS-8.0         | 27189217 |
| ECLASS-9.0         | 27189217 |
| ECLASS-10.1        | 27182806 |
| ECLASS-11.1        | 27182806 |
| ECLASS-12.0        | 27182806 |
| ETIM-5.0           | EC002625 |

|      |               |
|------|---------------|
| GTIN | 4048879035279 |
|------|---------------|

|                  |          |
|------------------|----------|
| Pakkestørrelse   | 1        |
| Tolltariffnummer | 85389099 |

**Frame**

|                                               |                       |
|-----------------------------------------------|-----------------------|
| Degree of protection (EN IEC 60529)           | IP65                  |
| Operating temperature min.                    | -10 °C                |
| Operating temperature max.                    | 60 °C                 |
| Storage temperature min.                      | -25 °C                |
| Storage temperature max.                      | 60 °C                 |
| Suitable for installation wall thickness min. | 1 mm                  |
| Suitable for installation wall thickness max. | 5 mm                  |
| Coating housing                               | surface finished      |
| Material housing                              | Fine zinc die casting |

**Germany (VDE)**

|                               |                    |
|-------------------------------|--------------------|
| Connection cross section max. | 6 mm <sup>2</sup>  |
| AWG number max.               | 10                 |
| Operating voltage AC          | 250 V              |
| Operating current             | 16 A               |
| Status indication LED         | yellow             |
| Connection                    | Screw terminals SK |
| No. of poles                  | 2 + PE             |
| Connections per pole          | 2                  |
| Protection contact present    | yes                |