

**Signal tower Modlight70 Pro equipped with LED modules**

white,blue,green ,red and buzzer, M12 plug downward

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27371230      |
| ECLASS-6.1       | 27371230      |
| ECLASS-7.0       | 27371230      |
| ECLASS-8.0       | 27371230      |
| ECLASS-9.0       | 27371230      |
| ECLASS-10.1      | 27371230      |
| ECLASS-11.1      | 27371230      |
| ECLASS-12.0      | 27371230      |
| ETIM-5.0         | EC001042      |
| GTIN             | 4048879825382 |
| Pakkestørrelse   | 1             |
| Tolltariffnummer | 85318070      |

**Electrical data | Supply**

|                           |        |
|---------------------------|--------|
| Operating voltage DC      | 24 V   |
| Operating voltage DC min. | 21,6 V |
| Operating voltage DC max. | 26,4 V |
| Current consumption max.  | 430 mA |

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Color housing    | black   |
| Material housing | Plastic |

**Mechanical data | Mounting data**

|        |        |
|--------|--------|
| Height | 334 mm |
|--------|--------|

|       |       |
|-------|-------|
| Width | 70 mm |
|-------|-------|

|       |       |
|-------|-------|
| Depth | 70 mm |
|-------|-------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
|----------------------------|--------|

|                            |       |
|----------------------------|-------|
| Operating temperature max. | 50 °C |
|----------------------------|-------|

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -30 °C |
|--------------------------|--------|

|                          |       |
|--------------------------|-------|
| Storage temperature max. | 60 °C |
|--------------------------|-------|

**Connection type 2**

|                          |     |
|--------------------------|-----|
| Family construction form | M12 |
|--------------------------|-----|

|        |      |
|--------|------|
| Gender | male |
|--------|------|

|        |   |
|--------|---|
| Coding | A |
|--------|---|

|              |   |
|--------------|---|
| No. of poles | 8 |
|--------------|---|

|       |               |
|-------|---------------|
| PIN 1 | 24 V DC (0 V) |
|-------|---------------|

|       |              |
|-------|--------------|
| PIN 2 | LED-Modul RD |
|-------|--------------|

|       |               |
|-------|---------------|
| PIN 3 | 0 V (24 V DC) |
|-------|---------------|

|       |              |
|-------|--------------|
| PIN 4 | LED-Modul CL |
|-------|--------------|

|       |              |
|-------|--------------|
| PIN 5 | LED-Modul YE |
|-------|--------------|

|       |              |
|-------|--------------|
| PIN 6 | LED-Modul BU |
|-------|--------------|

|       |              |
|-------|--------------|
| PIN 7 | LED-Modul GN |
|-------|--------------|

|       |   |
|-------|---|
| PIN 8 | - |
|-------|---|

|                 |                 |
|-----------------|-----------------|
| Mounting method | bayonet-locking |
|-----------------|-----------------|