



M12 male 0° B-cod. IDC

2-pol., 0,25 - 0,34mm², 4,5 - 8,8mm, shielded

PROFIBUS
Male straight
M12, 2-pole
B-coded
shielded
IDC terminals

[Link til produkt](#)

Illustrasjon



Produktet kan avvike fra bildet



Side 1

Family construction form	M12
Degree of protection (EN IEC 60529)	IP67

Handelsinformasjon

ECLASS-6.0	27279221
------------	----------

ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	27440102
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ETIM-5.0	EC002635
GTIN	4048879331739
Pakkestørrelse	1
Tolltariffnummer	85366990

Electrical data | Supply

Operating voltage AC max.	32 V
Operating voltage DC max.	32 V
Current operating per contact max.	4 A

Installation

Connection cross section min.	0,25 mm ²
Connection cross section max.	0,34 mm ²
AWG number min.	24
AWG number max.	22

Installation | Connection

Wire insulation diameter min.	2 mm
Wire insulation diameter max.	2,6 mm

Device protection | Electrical

Additional condition protection degree	inserted, screwed
--	-------------------

Mechanical data | Mounting data

Clamping range min.	4,5 mm
Clamping range max.	8,8 mm

Environmental characteristics | Climatic

Operating temperature min.	-25 °C
Operating temperature max.	85 °C