

## M12 male 0° A-cod. / MSUD valve plug B-10mm

PUR 3x0.75 bk UL/CSA 3m

Form B (10 mm) – M12, male straight

24 V AC  $\pm 20\%$  / DC  $\pm 25\%$

LED and suppression

Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

### [Link til produkt](#)

#### Illustrasjon





Produktet kan avvike fra bildet



|                                           |               |
|-------------------------------------------|---------------|
| Cable length                              | 3 m           |
| Side 1                                    |               |
| Tightening torque                         | 0,6 Nm        |
| Family construction form                  | M12           |
| Thread                                    | M12 x 1       |
| suitable for corrugated tube (internal Ø) | 10 mm         |
| Coding                                    | A             |
| No. of poles                              | 3             |
| Width across flats                        | SW13          |
| Degree of protection (EN IEC 60529)       | IP67          |
| Side 2                                    |               |
| Tightening torque                         | 0,4 Nm        |
| Family construction form                  | MSUD B        |
| Thread                                    | M3            |
| No. of poles                              | 3             |
| Degree of protection (EN IEC 60529)       | IP67          |
| Handelsinformasjon                        |               |
| ECLASS-6.0                                | 27279218      |
| ECLASS-6.1                                | 27279218      |
| ECLASS-7.0                                | 27279218      |
| ECLASS-8.0                                | 27279218      |
| ECLASS-9.0                                | 27060312      |
| ECLASS-10.1                               | 27060312      |
| ECLASS-11.1                               | 27060312      |
| ECLASS-12.0                               | 27060312      |
| ETIM-5.0                                  | EC001855      |
| GTIN                                      | 4048879315425 |
| Pakkestørrelse                            | 1             |
| Tolltariffnummer                          | 85444290      |
| Electrical data                           |               |
| Capacity CX                               | 20 ms         |
| Electrical data   Supply                  |               |

|                                    |        |
|------------------------------------|--------|
| Operating voltage AC               | 24 V   |
| Operating voltage AC min.          | 19,2 V |
| Operating voltage AC max.          | 28,8 V |
| Operating voltage DC               | 24 V   |
| Operating voltage DC min.          | 18 V   |
| Operating voltage DC max.          | 30 V   |
| Cut-off peak voltage max.          | 55 V   |
| Current operating per contact max. | 4 A    |

**Diagnostics**

|                       |        |
|-----------------------|--------|
| Status indication LED | yellow |
|-----------------------|--------|

**Device protection | Electrical**

|                                        |                   |
|----------------------------------------|-------------------|
| Additional condition protection degree | inserted, screwed |
| Rated surge voltage                    | 0,8 kV            |
| Material group (IEC 60664-1)           | I                 |
| Additional suppressor                  | Z-Diode           |

**Mechanical data | Material data**

|                       |                  |
|-----------------------|------------------|
| Coating locking       | Nickeled         |
| Locking screw coating | verzinkt         |
| Color housing         | black            |
| Material housing      | Plastic          |
| Locking material      | Zinc die-casting |

**Mechanical data | Mounting data**

|                 |                   |
|-----------------|-------------------|
| Mounting method | inserted, screwed |
|-----------------|-------------------|

**Environmental characteristics | Climatic**

|                                        |                            |
|----------------------------------------|----------------------------|
| Operating temperature min.             | -25 °C                     |
| Operating temperature max.             | 85 °C                      |
| Additional condition temperature range | depending on cable quality |

**Conformity**

|                  |                                                    |
|------------------|----------------------------------------------------|
| Product standard | DIN EN 61076-2-101 (M12), DIN EN 175301-803 (MSUD) |
|------------------|----------------------------------------------------|

**Installation | Cable**

|                                          |                                                  |
|------------------------------------------|--------------------------------------------------|
| Cable identification                     | 626                                              |
| Cable Type                               | 2                                                |
| Printing color of wire insulation        | white (isolation black)                          |
| Jacket Color                             | black                                            |
| Type of Certificate                      | cURus                                            |
| Amount stranding                         | 1                                                |
| Stranding                                | 3 wires twisted                                  |
| wire arrangement                         | black 1, black 2, green-yellow                   |
| No. of bending cycles (C-track)          | 2 Mio. @ 25 °C                                   |
| Cable weight                             | 55,33 g/m                                        |
| Material jacket                          | PUR                                              |
| Shore hardness jacket                    | 85 ± 5 Shore A                                   |
| Freedom from ingredients (jacket)        | lead-free, cadmium-free, CFC-free, silicone-free |
| Outer-diameter (jacket)                  | 5,9 mm                                           |
| Tolerance outer diameter (sheath)        | ± 5 %                                            |
| Material inner jacket                    | PVC                                              |
| Material wire insulation                 | PVC                                              |
| Amount wires                             | 3                                                |
| Outer diameter insulation                | 1,8 mm                                           |
| Outer diameter tolerance core insulation | ± 5 %                                            |
| Shore hardness wire insulation           | 43 ± 5 Shore D                                   |

|                                                         |                                                  |
|---------------------------------------------------------|--------------------------------------------------|
| Ingredient freeness wire insulation                     | lead-free, cadmium-free, CFC-free, silicone-free |
| Printing color of wire insulation                       | white (isolation black)                          |
| Amount strands (wire)                                   | 42                                               |
| Diameter of single wires                                | 0,15 mm                                          |
| Conductor crosssection (wire)                           | 0,75 mm <sup>2</sup>                             |
| Material conductor wire                                 | Stranded copper wire, bare                       |
| Conductor type (wire)                                   | strand class 6                                   |
| Traversing distance (C-track)                           | 5 m @ 25 °C   horizontal                         |
| Current load capacity (standard)                        | to DIN VDE 0298-4                                |
| Current load capacity min. wire                         | 12 A                                             |
| Electrical resistance line constant wire                | 26 Ω/km @ 20 °C                                  |
| Nominal voltage power AC max.                           | 300 V                                            |
| Power frequency withstand voltage power (wire - jacket) | 2 kV @ 60 s                                      |
| AC withstand voltage power (wire - wire)                | 2 kV @ 60 s                                      |
| Min. operating temperature (static)                     | -30 °C                                           |
| Max. operating temperature (fixed)                      | 80 °C                                            |
| Operating temperature min. (dynamic)                    | -5 °C                                            |
| Operating temperature max. (dynamic)                    | 80 °C                                            |
| chemical resistance                                     | Good, application-related testing                |
| Gasoline resistance                                     | Good, application-related testing                |
| Oil resistance                                          | DIN EN 60811-404                                 |
| Bending radius (fixed)                                  | 10 x Outer diameter                              |
| Bending radius (dynamic)                                | 15 x Outer diameter                              |