

**M12 male 0° A-cod. / MSUD double valve A-18mm**

PUR 4x0.75 bk UL/CSA+drag ch. 1m

Form A (18 mm) – M12, connector at the rear

24 V AC  $\pm 20\%$  / DC  $\pm 25\%$ 

LED and suppression





Connection cable L = 200 mm


Bridged PE

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link til produkt](#)**Illustrasjon**



Produktet kan avvike fra bildet



|                                          |                            |
|------------------------------------------|----------------------------|
| Cable length                             | 1 m                        |
| Handelsinformasjon                       |                            |
| ECLASS-6.0                               | 27143423                   |
| ECLASS-6.1                               | 27279218                   |
| ECLASS-7.0                               | 27279218                   |
| ECLASS-8.0                               | 27279218                   |
| ECLASS-9.0                               | 27060312                   |
| ECLASS-10.1                              | 27060312                   |
| ECLASS-11.1                              | 27060312                   |
| ECLASS-12.0                              | 27060312                   |
| ETIM-5.0                                 | EC001855                   |
| GTIN                                     | 4048879325233              |
| Pakkestørrelse                           | 1                          |
| Tolltariffnummer                         | 85444290                   |
| Electrical data   Supply                 |                            |
| Operating voltage AC                     | 24 V                       |
| Operating voltage AC min.                | 19,2 V                     |
| Operating voltage AC max.                | 28,8 V                     |
| Operating voltage DC                     | 24 V                       |
| Operating voltage DC min.                | 18 V                       |
| Operating voltage DC max.                | 30 V                       |
| Current consumption max.                 | 15 mA                      |
| Device protection   Electrical           |                            |
| Pollution Degree                         | 3                          |
| Rated surge voltage                      | 0,8 kV                     |
| Material group (IEC 60664-1)             | I                          |
| Environmental characteristics   Climatic |                            |
| Operating temperature min.               | -25 °C                     |
| Operating temperature max.               | 85 °C                      |
| Additional condition temperature range   | depending on cable quality |
| Installation   Cable                     |                            |
| Cable identification                     | 637                        |

|                                                   |                                                                |
|---------------------------------------------------|----------------------------------------------------------------|
| Cable Type                                        | 3                                                              |
| Printing color of wire insulation                 | white (isolation black)                                        |
| Jacket Color                                      | black                                                          |
| Type of Certificate                               | cURus                                                          |
| Amount stranding                                  | 1                                                              |
| Stranding                                         | 4 wires twisted                                                |
| wire arrangement                                  | black 1, black 2, black 3, green-yellow                        |
| Cable weight                                      | 69,3 g/m                                                       |
| Material jacket                                   | PUR                                                            |
| Shore hardness jacket                             | 90 ± 5 Shore A                                                 |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Outer-diameter (jacket)                           | 6,5 mm                                                         |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                          |
| Material wire insulation                          | PP                                                             |
| Amount wires                                      | 4                                                              |
| Outer diameter insulation                         | 1,85 mm                                                        |
| Outer diameter tolerance core insulation          | ± 5 %                                                          |
| Shore hardness wire insulation                    | 70 ± 5 Shore D                                                 |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Printing color of wire insulation                 | white (isolation black)                                        |
| Amount strands (wire)                             | 42                                                             |
| Diameter of single wires                          | 0,15 mm                                                        |
| Conductor crosssection (wire)                     | 0,75 mm²                                                       |
| Material conductor wire                           | Stranded copper wire, bare                                     |
| Conductor type (wire)                             | strand class 6                                                 |
| Traversing distance (C-track)                     | 10 m @ 25 °C   horizontal                                      |
| Travel speed (C-track)                            | 10 Mio. @ 25 °C                                                |
| Nominal voltage AC max.                           | 300 V                                                          |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                              |
| Current load capacity min. wire                   | 9,6 A                                                          |
| Electrical resistance line constant wire          | 26 Ω/km @ 20 °C                                                |
| AC withstand voltage (wire - wire)                | 2,5 kV @ 60 s                                                  |
| Power frequency withstand voltage (wire - jacket) | 2,5 kV @ 60 s                                                  |
| Min. operating temperature (static)               | -40 °C                                                         |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                              |
| Operating temperature min. (dynamic)              | -25 °C                                                         |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                              |
| UV resistance                                     | DIN EN ISO 4892-2 A                                            |
| Flame resistance                                  | UL 1581 § 1100 FT2   IEC 60332-2-2   UL 1581 § 1090            |
| chemical resistance                               | Good, application-related testing                              |
| Gasoline resistance                               | Good, application-related testing                              |
| Oil resistance                                    | DIN EN 60811-404   Good, application-related testing           |
| Bending radius (fixed)                            | 5 x Outer diameter                                             |
| Bending radius (dynamic)                          | 10 x Outer diameter                                            |
| No. of torsion cycles                             | 2 Mio.                                                         |
| Torsion speed                                     | 35 cycles/min                                                  |
| Torsion stress                                    | ± 180 °/m                                                      |