

**GigaBit crimp contact - F, 0,08-0,12 mm<sup>2</sup>**GigaBit crimp contact - F, 0,08-0,12 mm<sup>2</sup>

Turned crimp contact

Female

Technical data will be only guaranteed with Murrelektronik components.

[Link til produkt](#)**Illustrasjon**

Produktet kan avvike fra bildet

**Handelsinformasjon**

|                  |               |
|------------------|---------------|
| ECLASS-6.0       | 27261204      |
| ECLASS-6.1       | 27261202      |
| ECLASS-7.0       | 27440204      |
| ECLASS-8.0       | 27440204      |
| ECLASS-9.0       | 27440204      |
| ECLASS-10.1      | 27440204      |
| ECLASS-11.1      | 27440204      |
| ECLASS-12.0      | 27440204      |
| ETIM-5.0         | EC000796      |
| GTIN             | 4048879672870 |
| Pakkestørrelse   | 100           |
| Tolltariffnummer | 85366990      |

**Installation**

|                               |                      |
|-------------------------------|----------------------|
| Connection cross section min. | 0,08 mm <sup>2</sup> |
| Connection cross section max. | 0,12 mm <sup>2</sup> |
| AWG number min.               | 28                   |
| AWG number max.               | 26                   |

**Installation | Connection**

|                    |        |
|--------------------|--------|
| Stripping length   | 4,2 mm |
| Connection         | Crimp  |
| Gender             | female |
| Mating cycles min. | 200    |

**Mechanical data | Material data**

|                  |              |
|------------------|--------------|
| Coating contact  | gold plated  |
| Material contact | Copper alloy |

**Mechanical data | Mounting data**

|        |         |
|--------|---------|
| Height | 1,7 mm  |
| Width  | 1,7 mm  |
| Depth  | 13,6 mm |