stay connected

## MICO BASIC 5.2/3.6 ELEC AUX CIRCUIT, 8 CHANNELS


IN: 24 V DC OUT: 24 V DC / 5x 2 A CL2 & 3x 6 A


MICO BASIC 5.2/3.6
8 channels
Current adjustment 5× 2 A; 3× 6 A

**Link til produkt**

### Illustrasjon






Produktet kan avvike fra bildet

### Handelsinformasjon

| | |
|---|---|
| ECLASS-6.0 | 27371802 |
| ECLASS-6.1 | 27371802 |
| ECLASS-7.0 | 27371802 |
| ECLASS-8.0 | 27371802 |
| ECLASS-9.0 | 27371802 |
| ECLASS-10.1 | 27371802 |
| ECLASS-11.1 | 27371802 |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.
All informasjon gis uten ansvar for eventuelle feil og mangler. 28.03.2024

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-12.0 | 27371802 |
| ETIM-5.0 | EC001440 |
| GTIN | 4048879382373 |
| Pakkestørrelse | 1 |
| Tolltariffnummer | 85363030 |
| **Electrical data \| Input** | |
| Input voltage DC | 24 V |
| Input voltage DC min. | 18 V |
| Input voltage DC max. | 30 V |
| ON input voltage control inputs min. | 10 V |
| ON input voltage control inputs max. | 30 V |
| ON pulse length control inputs high min. | 20 ms |
| Total current bridge set max. | 40 A |
| **Electrical data \| Output** | |
| Switch-on capacity per channel max. | 20 mF |
| Switching current max. | 20 mA |
| **Installation** | |
| Connection cross-section inputs max. | 16 mm² |
| Connection cross-section outputs max. | 4 mm² |
| Connection cross-section control inputs / control outputs max. | 2,5 mm² |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| Height | 90 mm |
| Width | 70 mm |
| Depth | 80 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | 0 °C |
| Operating temperature max. | 55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | 80 °C |
| **Connection type 7** | |
| Family construction form | Bridging Contact |
| Gender | female |
| Color contact carrier | black |
| No. of poles | 1 |
| PIN 1 | 24 V DC |
| Family construction form | Bridging Contact |
| Gender | female |
| Color contact carrier | black |
| No. of poles | 1 |
| PIN 1 | 0 V |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 1 |
| PIN 1 | 24 V DC |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.
All informasjon gis uten ansvar for eventuelle feil og mangler. 28.03.2024

| | |
|---|---|
| Color contact carrier | green |
| No. of poles | 1 |
| PIN 1 | 0 V |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 2 |
| PIN 1 | On |
| PIN 2 | 14 |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 4 |
| PIN 1 | Out 1 |
| PIN 2 | Out 2 |
| PIN 3 | Out 3 |
| PIN 4 | Out 4 |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 4 |
| PIN 1 | Out 5 |
| PIN 2 | Out 6 |
| PIN 3 | Out 7 |
| PIN 4 | Out 8 |

Opplysningene i dette databladet er utarbeidet med størst mulig omhu.
All informasjon gis uten ansvar for eventuelle feil og mangler. 28.03.2024